

## **SIDEWALK RAMP RETROFIT**

### **Description**

This work consists of installing a sidewalk ramp with cement concrete curb and hot mix asphalt, at the locations shown in the Plans or where designated by the Engineer in accordance with these specifications and in conformity to the lines and grades as staked.

### **Materials**

Materials shall meet the applicable portions of Section 5-04, for commercial HMA asphalt and Section 8-04 for cement concrete curbs. In addition, embankment material required to provide an acceptable base for the ramp shall meet the requirements of Section 2-03.3(14).

### **Construction Requirements**

When installing the sidewalk ramp where existing asphalt shoulders are present, the Contractor shall saw cut and remove the pavement to the neat lines shown in the plans. The Contractor may use the removed material in the construction of the base for the ramp or dispose of the asphalt off of the State's Right of Way. No waste site has been provided for this work and the Contractor shall dispose of the excavated material in accordance with state and local agency ordinances and regulations.

### **Measurement**

The sidewalk ramp retrofit will be measured by the square yard of finished surface and will include the top of the cement concrete curb. Embankment material required to construct the base for the ramp will be measured by the ton in the hauling vehicle.

### **Payment**

Payment will be made in accordance with Section 1-04.1, for each of the following bid items that are included in the proposal:

“Sidewalk Ramp Retrofit”, per square yard.

“Select Borrow Incl. Haul”, per ton.

All costs involved in cutting, removing and disposing of existing asphalt pavement, furnishing and installing the cement concrete curb and hot mix asphalt, and shaping the select borrow base will be included in the bid item “Sidewalk Ramp Retrofit”.