

Last revised on : 07/10/2020

S \mathcal{O} \geq СЛ

Ø

-END OF GIRDER - - - - -— ОАК BLOCK 🤇 1 В3 В4

OAK BLOCK DETAIL

ELEVATION AT TOP

OF OAK BLOCK			
GIRDER	PIER?		
	BACK STATION	AHEAD STATION	

DIAPHRAGM NOTES:

- 1. GIRDERS SHALL BE HELD RIGIDLY IN PLACE WHEN DIAPHRAGMS
- 2. CUT/RELEASE GIRDER TEMPORARY STRANDS BEFORE CASTING DIAPHRAGM AND BRIDGE DECK. SEE TEMPORARY STRAND CUTTING SEQUENCE.
- 3. EXTENDED STRANDS AND GIRDER REINFORCING NOT SHOWN
- 4. LONGITUDINAL DIMENSIONS ARE NORMAL TO € DIAPHRAGM
- 5. FOR CONCRETE PLACEMENT PROCEDURE SEE "SUPERSTRUCTURE CONSTRUCTION SEQUENCE" SHEET.

PLACED PARALLEL TO FACE OF CROSSBEAM, FULL WIDTH OF BOTTOM FLANGE, TO REMAIN IN PLACE. HEIGHT SHALL NOT EXCEED WIDTH AT € GIRDER.

portation	STANDARD PRESTRESSED CONCRETE GIRDERS	SHEET NO. SHEET
-	WF THIN DECK GIRDER DIAPHRAGM AT INTERMEDIATE PIER DETAILS	OF