

Last revised on : 07/10/2020

Ω 0 AΒ

4

ELEVATION AT TOP OF OAK BLOCK AT € GIRDER

GIRDER	PIER ?		
	BACK STATION	AHEAD STATION	

DIAPHRAGM NOTES:

	1.	CUT/RELEASE GIRDER TEMPORARY STRANDS BEFORE CASTING DIAPHRAGM AND BRIDGE DECK. SEE TEMPORARY STRAND CUTTING SEQUENCE.			
	2.	2. EXTENDED STRANDS AND GIRDER REINFORCING NOT SHOWN FOR CLARITY.			
	3. LONGITUDINAL DIMENSIONS ARE NORMAL TO € PIER.				
	4. FOR CONCRETE PLACEMENT PROCEDURE SEE "SUPERSTRUCTURE CONSTRUCTION SEQUENCE" SHEET.				
NOTES:					
VARY HEIGHT AS NECESSARY TO PROVIDE UNIFORM BEARING FULL WIDTH OF GIRDER.					
2 FULL WIDTH OF GIRDER. REMOVE AFTER PLACING TRAFFIC BARRIER.					
	3	ight angle alternate 135° hook every other bar			
	PR	STANDARD ESTRESSED CONCRETE GIRDERS	BRIDGE SHEET NO.		
tion			SHEET		
		SLAB GIRDER FIXED DIAPHRAGM	SHEETS		