



Contract Number \_\_\_\_\_

HMA mix design ID number(s) to be used for production of WMA \_\_\_\_\_

**WMA Technology Description**

Name of WMA additive manufacturer or producer \_\_\_\_\_

Description of project or process \_\_\_\_\_

Water/Foaming      Organic Additive      Chemical Additive      Other \_\_\_\_\_

Manufacturer or producer's recommended WMA additive dosage rate \_\_\_\_\_

Contractor's target WMA additive dosage rate \_\_\_\_\_

<b>Manufacturer or Producer's Recommendation</b>	<b>Temperature (°F)</b>
Maximum mixing temperature for HMA when using WMA additive	_____
Maximum discharge temperature for HMA when using WMA additive	_____
Maximum asphalt binder temperature when using WMA additive	_____

\*The Contractor's maximum mixing temperature cannot exceed the maximum mixing temperature recommended by the manufacturer of the WMA additive nor the optimum mixing temperature +25°F per Section 5-04.3(8).

Submitted by \_\_\_\_\_

Paving Contractor

Paving Contractor Representative - Signature

Approved by

Contracting Agency Representative - Signature

Reminder: The truck ticket shall identify the material produced as "WMA" when using WMA products or processes.

Required Attachments:

WMA Additive Manufacturer's catalog cuts

WMA Additive Manufacturer's Recommendations for production