

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49

DIVISION5.GR5 SURFACE TREATMENTS AND PAVEMENTS

04.GR5 ASPHALT CONCRETE PAVEMENT

0403.GR5 Construction Requirements

040314.GR5 Planing Bituminous Pavement

BSP0403147.FB5 (Removing Top Layer of Pavement Surfacing Overlay From Bridge Deck) (BSP October 13, 2003)
Use in projects where the top layer of existing pavement surfacing overlay is being removed from a bridge deck with an existing waterproofing membrane that is to remain and be protected from damage. The fill-in specifies the bridge(s) requiring the work. Include with **BSP04049.GB5 and BSP04059.GB5** when the work is covered by a separate stand-alone bid item instead of being incidental to the overall surfacing planing.
(1 fill-in)

BSP0403148.FB5 (Removing Top Layer of Pavement Surfacing Overlay From Bridge Deck) (BSP October 13, 2003)
Use in projects where the top layer of existing pavement surfacing overlay is being removed from a bridge deck without an existing waterproofing membrane. The fill-in specifies the bridge(s) requiring the work. Include with **BSP04049.GB5 and BSP04059.GB5** when the work is covered by a separate stand-alone bid item instead of being incidental to the overall surfacing planing.
(1 fill-in)

BSP0403149.FB5 (Removing Pavement Surfacing Overlay From Bridge Deck) (BSP October 13, 2003)
Use in projects where the existing pavement surfacing overlay is being completely removed from a bridge deck. The fill-in specifies the bridge(s) requiring the work. Include with **02250.GB6, 023106.GB6, and either 02516.GB6, or 02415.GB6 and 02515.GB6.** Include with **BSP04049.GB5 and BSP04059.GB5** when the work is covered by a separate stand-alone bid item instead of being incidental to the overall surfacing planing.
(1 fill-in)

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31

[BSP04031410.FB5](#) (Planing of Pavement in the Vicinity of Bridge Expansion Joint Headers)
(BSP April 7, 2008)
Use in projects where bridge expansion joints and headers within the limits of pavement planing over bridge decks are to remain in place undamaged by the pavement planing operations.
(1 fill-in)

[0404.GR5](#)

Measurement

[BSP04049.GB5](#) (Removing Existing Overlay From Bridge Deck)
(BSP October 13, 2003)
Use in projects where the existing pavement surfacing overlay is being removed from a bridge deck when the work is covered by a separate stand-alone bid item instead of being incidental to the overall surfacing planing. Include with ***BSP04059.GB5, and either BSP0403147.FB5, BSP0403148.FB5, or BSP0403149.FB5.***

[0405.GR5](#)

Payment

[BSP04059.GB5](#) (Removing Existing Overlay From Bridge Deck)
(BSP October 13, 2003)
Use in projects where the existing pavement surfacing overlay is being removed from a bridge deck when the work is covered by a separate stand-alone bid item instead of being incidental to the overall surfacing planing. Include with ***BSP04049.GB5, and either BSP0403147.FB5, BSP0403148.FB5, or BSP0403149.FB5.***