

(November 20, 2023)

Longitudinal Seismic Restrainers

The Contractor shall submit Type 1 Working Drawings consisting of shop drawings of the steel components of the longitudinal seismic restrainer assemblies in accordance with Section 6-03.3(7).

The Contractor shall core drill holes through the pier diaphragm for the highstrength steel bar as shown in the Plans. The Contractor shall set the PVC pipe in place with epoxy bonding agent as shown in the Plans.

Holes for the resin bonded anchors for the longitudinal seismic restrainer anchorages shall be located and drilled in accordance with Section 6-02.3(18)A, and as follows:

- The bottom layer of steel reinforcing bars in the slab in the vicinity of the longitudinal seismic restrainer anchorage as shown in the Plans shall be located and marked on the concrete surface.
- 2. Using the anchorage assembly as a template, the Contractor shall align and slightly shift the anchorage assembly as required so that the holes avoid the existing steel reinforcing bars.
- 3. The Contractor shall drill holes for the resin bonded anchors with the anchorage assembly in position as a template.
- 4. If, after shifting the anchorage assembly, conflicts still exist between hole locations and existing steel reinforcing bars, the Contractor may, with the Engineer's approval, core drill holes at the conflict locations.

The surface of the concrete in contact with the anchorage assembly shall be coated with Type II epoxy bonding agent conforming to Section 9-26.2, with the grade and class as recommended by the epoxy bonding agent manufacturer. The longitudinal seismic restrainer anchorage assembly shall be set in place within the set time specified in the manufacturer's data sheet for the epoxy bonding agent.

All longitudinal seismic restrainers at a pier shall be installed so that the free end (the end with the gap as shown in the Plans) shall be on the same side of the pier.