

1 (January 7, 2019)

2 **Polyester Concrete**

3 **Manufacturer's Technical Representative**

4 The Contractor shall have the services of a qualified polyester concrete
5 manufacturer's technical representative physically present at the job site. The
6 manufacturer's technical representative shall assist the Contractor in training the
7 Contractor's personnel and providing technical assistance in preparing the header
8 blackout surface, applying primer, and mixing, placing, and curing the polyester
9 concrete.

10
11 **Mix Design**

12 Polyester concrete shall be composed of the following three components –
13 polyester resin binder, high molecular weight methacrylate (HMWM) resin, and
14 aggregate, in accordance with Section 6-02.2 as supplemented in these Special
15 Provisions.

16
17 The Contractor shall prepare and submit a Type 1 Working Drawing consisting of
18 the polyester concrete design mix and mixing procedure. The mix design shall
19 include a recommended initiator percentage for the expected application
20 temperature, and the recommended amount of polyester resin binder as a
21 percentage of the dry weight of aggregate. The amount of peroxide initiator used
22 shall result in a polyester concrete set time between 30 and 120 minutes during
23 placement as determined by California Test 551, Part 2, "Method of Test For
24 Determination of Set Time of Concrete Overlay and Patching Materials", by Gilmore
25 Needles. Accelerators or inhibitors may be required as recommended by the
26 polyester resin binder supplier.

27
28 **Delivery and Storage of Materials**

29 All materials shall be delivered in their original containers bearing the
30 manufacturer's label, specifying date of manufacturing, batch number, trade name
31 brand, and quantity. Each shipment of polyester resin binder and HMWM resin
32 shall be accompanied by a Safety Data Sheet (SDS).

33
34 The material shall be stored in accordance with the manufacturer's
35 recommendations.

36
37 Sufficient material to perform the entire polyester concrete application shall be in
38 storage at the site prior to any field preparation.

39
40 **Equipment and Containment**

41 The Contractor shall submit a Type 1 Working Drawing consisting of all equipment
42 for cleaning the concrete and steel surfaces, and mixing and applying the polyester
43 concrete.

44
45 The HMWM resin, and abrasive blasting materials, shall be contained and
46 restricted to the surface receiving the polyester concrete only, and shall not escape
47 to the surrounding environment. The Contractor shall submit a Type 1 Working
48 Drawing consisting of the method and materials used to collect and contain the
49 HMWM resin, and abrasive blasting materials.

50

Surface Preparation

The concrete and steel surfaces shall be prepared by removing all material which may act as a bond breaker between the surface and the polyester concrete. Surface cleaning shall be by abrasive blasting. Precautions shall be taken to ensure that no dust or debris leaves the bridge deck and that all traffic is protected from rebound and dust.

If the concrete or steel surfaces become contaminated, the contaminated areas shall be recleaned by abrasive blasting.

Application of Prime Coat

Application of the HMWM prime coat and the polyester concrete shall not begin if rain is forecast within 12-hours of completion of the Work. The area receiving the prime coat shall be dry and had no rain within the past 12 hours. Immediately prior to applying the prime coat, the surfaces shall be cleaned to remove accumulated dust and any other loose material.

The concrete bridge deck surface shall be between 50F and 85F when applying the prime coat.

The Contractor shall apply one coat of promoted/initiated wax-free HMWM resin to the prepared concrete and steel surfaces immediately before placing the polymer concrete. The promoted/initiated resin shall be worked into the concrete in a manner to assure complete coverage of the area receiving polyester concrete. A one pint sample of each batch of promoted/initiated HMWM resin shall be retained and submitted to the Engineer at the time of primer application.

The prime coat shall cure for 30 minutes minimum before beginning placement of the polyester concrete. Placement of the polymer concrete shall not proceed until the Engineer verifies that the HMWM resin was properly promoted and initiated, as evidenced by the HMWM batch sample.

If the primed surface becomes contaminated, the contaminated area shall be cleaned by abrasive blasting and reprimed.

Mixing Equipment for Polyester Concrete

Polyester concrete shall be mixed in mechanically operated mixers in accordance with the mix design as approved by the Engineer. The mixer size shall be limited to a nine cubic yard maximum capacity, unless otherwise approved by the Engineer.

The aggregate and resin volumes shall be recorded for each batch along with the date of each recording. A printout of the recordings shall be furnished to the Engineer at the end of each work shift.

The Contractor shall prevent any cleaning chemicals from reaching the polyester mix during the mixing operations.

Mixing Components

The polyester resin binder in the polyester modified concrete shall be approximately 12 percent by weight of the dry aggregate. The Contractor shall specify the exact percentage in the mix design Working Drawing submittal.

1 The polyester resin binder shall be initiated and thoroughly blended just prior to
2 mixing the aggregate and binder. The polyester concrete shall be thoroughly mixed
3 prior to placing.
4

5 **Polyester Concrete Placement**

6 The polyester concrete shall be placed within two hours of placing the prime coat.
7

8 Polyester concrete shall be placed within 15 minutes following initiation. Polyester
9 concrete that is not placed within this time shall be discarded.
10

11 The surface temperature of the area receiving the polyester concrete shall be the
12 same as specified above for the HMWM prime coat.
13

14 The polyester concrete shall be consolidated in accordance with the manufacturer's
15 recommendations.
16

17 **Finished Polyester Concrete Surface**

18 The finished surface of the polyester concrete shall be smooth and uniform as to
19 crown and grade in accordance with Section 6-02.3(10)D3.
20

21 Finishing equipment used shall strike off the polyester concrete to the established
22 grade and cross section.
23

24 The polyester concrete shall receive an abrasive sand finish. The sand finish shall
25 be applied by hand immediately after strike-off and before gelling occurs. Sand
26 shall be broadcast onto the surface to affect a uniform coverage of a minimum of
27 0.8 pounds per square yard.
28

29 **Curing**

30 The polyester concrete shall be cured in accordance with the manufacturer's
31 recommendations. The Contractor shall measure the compressive strength of the
32 cured polyester concrete with a rebound hammer in accordance with ASTM C 805.
33 The readings of the rebound hammer used shall be correlated to the compressive
34 strength of the polyester concrete product in accordance with ASTM C 805 Section
35 5.4, and the Contractor shall submit a Type 1 Working Drawing of this correlation.
36

37 Traffic and equipment shall not be permitted on the polyester concrete until it
38 achieves a compressive strength of 2500 psi based on the rebound hammer
39 readings and the correlation chart for the rebound hammer used.