(April 6, 2015)

Light Standards with Type 1 Luminaire Arms

Lighting standards shall be fabricated in conformance with the methods and materials specified on the pre-approved Plans listed below, provided the following requirements have been satisfied:

(a) Light source to pole base distance (H1) shall be as noted in the Plans. Verification of H1 distances by the Engineer, prior to fabrication, is not required. Fabrication tolerance shall be ± 6 inches.

(b) All other requirements of the Special Provisions have been satisfied.

Pre-Approved Plan	Fabricator	Mounting Hgt.
Drawing No. DB00654 Rev. H Sheets 1, 2, 3 & 4	Valmont Ind. Inc.	30', 35', 40' & 50'
Drawing No. W3721-1 Rev. L & W3721-2 Rev. E	Ameron Pole Prod. Div.	20',25',30',35',40', 45' & 50'
Drawing No. NWS 3510 Rev. 2 or NWS 3510B Rev. 2	Northwest Signal Supply, Inc.	25', 30', 35', 40', 45' & 50'
Drawing WS-SL-01 Revision 7 Sheets 1 & 2 of 2	American Pole Structures, Inc.	25', 30', 35', 40', 45', 50'
Drawing 71035-B39 Rev. R11 Sheets 1 & 2 of 2	Union Metal Corp	40'
Drawing 71035-B50 Rev. R4 Sheets 1, 2 & 3 and B100-B335 Rev. R1	Union Metal Corp.	50'
Drawing 71035-B47 Rev. R3 Sheet 1 of 1 Elbow Mounting Detail	Union Metal Corp	40', 50'
Drawing No. WSDOT-LP-01 Rev. 4, Sheets 1 and 2 or WSDOT - LP-01-BE Rev 3 Sheets 1 and 2 or WSDOT - LP-01-C8B Rev 2	West Coast Engineering Group	25', 30', 35', 40', 45', and 50'
Drawing No. 10-31-RWP-1 Rev. 7 Sheets 1, 2 & 3	KW Industries	25, 30, 35, 40, 45, 50
Drawing No. 10-31-RWP-3 Rev. 2	KW Industries	

1 (Bridge Mount Details)