

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36

**(April 6, 2015)**

**Light Standards with Type 2 Luminaire Arms**

Lighting standards shall be fabricated in conformance with the methods and materials specified on the pre-approved Plans listed below, provided the following requirements have been satisfied:

(a) Light source to pole base distance (H1) shall be as noted in the Plans. Verification of H1 distances by the Engineer, prior to fabrication, is not required. Fabrication tolerance shall be  $\pm 6$  inches.

(b) All other requirements of the Special Provisions have been satisfied.

<u>Pre-Approved Plan</u>	<u>Fabricator</u>	<u>Mounting Hgt.</u>
Drawing No. DB00653 Rev. H Sheets 1, 2, 3 & 4	Valmont Ind. Inc.	30', 35', 40' & 50'
Drawing No. W3720-1 Rev. K & W3720-2 Rev. E	Ameron Pole Prod. Div.	30', 35' 40' 45' & 50'
Drawing No. NWS 3515 Rev. 2 or NWS 3515B Rev. 2	Northwest Signal Supply, Inc.	25', 30', 35', 40', 45' & 50'
Drawing WS-SL-02 Rev. 7 Sheets 1 & 2 of 2	American Pole Structures, Inc.	25', 30', 35', 40', 45', 50'
Drawing No. WSDOT-LP-02 Rev. 3, Sheets 1 and 2 or WSDOT - LP-01-BE Rev 3 Sheets 1 and 2 or WSDOT - LP-01-C8B Rev 2	West Coast Engineering Group	25', 30', 35', 40', 45', and 50'
Drawing No. 10-31-RWP-2 Rev. 8 Sheet 1, 2, & 3	KW Industries	25', 30', 35', 40' 45' and 50'