

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38

(August 1, 2016)

Light Standards with Type 2 Luminaire Arms

Lighting standards shall be fabricated in conformance with the methods and materials specified on the pre-approved Plans listed below, provided the following requirements have been satisfied:

- (a) Mounting heights shall be as specified in the Plans.
- (b) Light source to pole base distance (H1) shall be determined or verified by the Engineer, prior to fabrication. Fabrication tolerance shall be ± 6 inches.
- (c) All other requirements of the Special Provisions have been satisfied.

<u>Pre-Approved Plan</u>	<u>Fabricator</u>	<u>Mounting Hgt.</u>
Drawing No. DB00653 Rev. H Sheets 1, 2, 3 & 4	Valmont Ind. Inc.	30', 35', 40' & 50'
Drawing No. W3720-1 Rev. K W3720-2 Rev. E	Ameron Pole Prod. Div.	30', 35', 40', 45' & 50'
Drawing No. NWS 3515 Rev. 2 or NWS 3515B Rev. 2	Northwest Signal Supply, Inc.	25', 30', 35', 40', 45' & 50'
Drawing WS-SL-02 Rev. 7 Sheets 1 & 2 of 2	American Pole Structures, Inc.	25', 30', 35', 40', 45', 50'
Drawing No. WSDOT-LP-02 Rev. 3, Sheets 1 and 2 or WSDOT - LP-01-BE Rev 3 Sheets 1 and 2 or WSDOT - LP-01-C8B Rev 2	West Coast Engineering Group	25', 30', 35', 40', 45', and 50'
Drawing No. 10-31-RWP-2 Rev. 8 Sheet 1,2, & 3	KW Industries	25', 30', 35', 40', 45' and 50'