WASHINGTON STATE HIGHWAY DEPARTMENT RESEARCH PROGRAM REPORT **13.1A**

# ATTENUATION OF RANDOM DEEP WATER WAVES BY A POROUS WALLED BREAKWATER: APPENDICES

RESEARCH PROJECT
Y-1307



August 1973

PREPARED FOR
WASHINGTON STATE HIGHWAY COMMISSION
IN COOPERATION WITH
U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL HIGHWAY ADMINISTRATION

E.P. RICHEY
D.B. MORDEN, B.J. HARTZ
C.W. HARRIS HYDRAULIC LABORATORY
DEPT. OF CIVIL ENGINEERING
UNIVERSITY OF WASHINGTON

HIGHWAY DEPT. LIBRARY

WA STATE DOT LIBRARY
3 3166 0002 4434 3

# APPENDIX I

Representative records of various chamber and wind conditions are grouped in order of increasing observed wind speed. For each condition the wind speed direction, chamber width, date, number of data points used in the spectral analysis and the calculated attenuation are listed. A table is presented showing the variance in the spectral peak frequencies, peak frequencies and any secondary peaks which may occur are shown for the force and pressure transducers. For each case, normalized smooth spectral estimates vs. frequency are shown for the superimposed pressure records. The frequency of the peak force is also indicated on the plot.

# FIVE FOOT WIDE CHAMBER

## (SOLID BOTTOM)

WINDSPEED: 10 mph. DIRECTION: South

CHAMBER WIDTH: 5 feet DATE: 5/15/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW)/REMOTE) 70.9%

RUN NUMBER: 12,S7,o NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 104.96 | 6.880 | .5488 | 722.12 | .8179 | .79 |
| BOTTOM | 127.06 | 7.139 | .5488 | 907.08 | .4547 | .79 |
| PRESSURES: REMOTE | .00055 | 6.742 | .5488 | .00371 | .8269<br>.3325<br>.1847 | .30<br>1.14<br>1.36 |
| IN FRONT OF CHAMBER | .00016 | 3.6791 | .5640 | .00059 | 1.7738<br>.1872<br>.2287 | .30<br>1.13<br>1.36 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 51


FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED
BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 52

WINDSPEED: 12-15 mph. DIRECTION: south

CHAMBER WIDTH: 5 feet DATE: 5/12/72

ATTENUATION (1- VARIANCE RATIO(CHAMBER(BW)/REMOTE)): 63.2%

RUN NUMBER: 11,S7,n NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 136.97 | 6.362 | .4878 | 871.40 | .5335 | .79 |
| BOTTOM | 223.05 | 7.161 | .4878 | 1597.26 | .2333 | .79 |
| PRESSURES: REMOTE | .00068 | 5.124 | .5335 | .00348 | .8483<br>.3224<br>.1155 | .27<br>1.11<br>1.36 |
| IN FRONT OF CHAMBER | .00025 | 4.366 | .4726 | .00109 | .8615<br>.2048<br>.1453 | .26<br>1.05<br>1.36 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 53

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 54

WINDSPEED: 15 mph. DIRECTION: South

CHAMBER WIDTH: 5 feet DATE: 5/12/72

ATTENUATION (1- VARIANCE RATIO(CHAMBER(BW)/REMOTE)): 58.1%

RUN NUMBER: 11,S7,m NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 245.48 | 6.750 | .4878 | 1659.99 | .3085 | .78 |
| BOTTOM | 429.61 | 7.533 | .4878 | 3236.25 | .1527 | .75 |
| PRESSURES: REMOTE | .00074 | 6.229 | .5183 | .00461 | .3838<br>.4354 | .32<br>.99 |
| IN FRONT OF CHAMBER | .00031 | 6.104 | .4573 | .00189 | .2553<br>.1348 | 1.04<br>1.36 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 55

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 56

WINDSPEED: 18-20 mph. DIRECTION: South

CHAMBER WIDTH: 5 feet DATE: 4/17/72

ATTENUATION (1- VARIANCE RATIO(CHAMBER(BW)/REMOTE)): 63.8%

RUN NUMBER: 14,S12,r NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 674.73 | 5.732 | .4878 | 3867.55 | .4409<br>.2410 | .21<br>.76 |
| BOTTOM | 1044.41 | 6.352 | .4726 | 6634.09 | .6492 | .14 |
| PRESSURES: REMOTE | .00708 | 3.068 | .4726 | .02172 | 1.8793<br>.8493 | .20<br>.96 |
| IN FRONT OF CHAMBER | .00256 | 4.185 | .4421 | .01071 | 3.0455 | .14 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS
FREQUENCY FOR SUPERPOSITION OF INCIDENT AND
REFLECTED WAVES (FIXED MONITORING STATIONS)
REMOTE STATION
IN FRONT OF CHAMBER
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 57


FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED
BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 58

WINDSPEED: 18-20 mph. DIRECTION: South

CHAMBER WIDTH: 5 feet DATE: 4/17/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW)/REMOTE)): 45.0%

RUN NUMBER: 14,S12,s NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 890.121 | 5.147 | .4573 | 4581.45 | .3149<br>.5821<br>.1963<br>.1007 | .14<br>.23<br>.78<br>1.17 |
| BOTTOM | 1252.17 | 5.848 | .4573 | 7322.69 | .2190<br>.4239<br>.1051 | .14<br>.23<br>.78 |
| PRESSURES: REMOTE | .00451 | 3.356 | .4726 | .01514 | .6102<br>1.0812<br>.4895<br>.9944<br>.4996 | .14<br>.23<br>1.01<br>1.17<br>1.34 |
| IN FRONT OF CHAMBER | .00248 | 5.117 | .4268 | .01269 | .6922<br>1.2614<br>.9054<br>.4954 | .14<br>.23<br>1.17<br>1.34 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS
FREQUENCY FOR SUPERIMPOSED INCIDENT AND
REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 59


FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED
BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG.60

WINDSPEED: 20 mph. DIRECTION: South south west

CHAMBER WIDTH: 5 feet DATE: 5/12/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW/REMOTE)): 54.2%

RUN NUMBER: 11,S6,1 NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 297.19 | 6.560 | .4726 | 1949.57 | .288 | .75 |
| BOTTOM | 522.33 | 7.342 | .4726 | 3834.95 | .1289 | .75 |
| PRESSURES: REMOTE | .00096 | 6.495 | .5031 | .00624 | .3459<br>.5865 | .32<br>1.01 |
| IN FRONT OF CHAMBER | .00044 | 7.182 | .4421 | .00316 | 1.1332<br>.2516 | .58<br>1.02 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 61

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG.62

WINDSPEED: 20 mph. DIRECTION: South south west

CHAMBER WIDTH: 5 feet DATE: 4/17/72

ATTENUATION (1- VARIANCE RATIO(CHAMBER(BW)/REMOTE)): 44.4%

RUN NUMBER: 13,S7,p NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 341.79 | 6.988 | .4878 | 2381.44 | .2959 | .76 |
| BOTTOM | 559.02 | 6.386 | .4726 | 3569.90 | None | |
| PRESSURES: REMOTE | .00196 | 5.046 | .4268 | .00989 | .3836<br>.2246 | .95<br>1.11 |
| IN FRONT OF CHAMBER | .00109 | 6.338 | .4421 | .00691 | .1294 | 1.02 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG.63




FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.

FIG.64

WINDSPEED: 20-25 mph. DIRECTION: South south west

CHAMBER WIDTH: 5 feet DATE: 4/17/71

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW)/REMOTE)): 56.3%

RUN NUMBER: 13,S7,q NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 547.71 | 5.884 | .4726 | 3222.75 | .2855 | .78 |
| BOTTOM | 592.39 | 6.470 | .4726 | 3832.76 | None | |
| PRESSURES: REMOTE | .00300 | 6.747 | .3963 | .02024 | .2379 | 1.01 |
| IN FRONT OF CHAMBER | .00131 | 6.119 | .41156 | .00802 | None | |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 65


FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED
BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 66

WINDSPEED: 30mph. DIRECTION: South

CHAMBER WIDTH: 5 feet DATE: 3/14/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW)/REMOTE)): 32.3%

RUN NUMBER: 5,S8,k NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: | | | | | | |
| TOP | | | | | | |
| Unfiltered | 1833.31 | 4.700 | .3963 | 8616.55 | .3567 | .66 |
| Filtered | 1543.52 | 5.213 | .3811 | 8046.40 | None | |
| BOTTOM | | | | | | |
| Unfiltered | 2516.36 | 5.52 | .3811 | 15,012.6 | None | |
| Filtered | 2375.66 | 5.966 | .3811 | 14,173.2 | None | |
| PRESSURES: | | | | | | |
| REMOTE | | | | | | |
| Unfiltered | .02872 | 2.647 | .3201 | .07602 | .2728 (9.29 folding at NYQ. Freq.) | .78 |
| Filtered | .01157 | 5.653 | .3201 | .06540 | .6573 | .79 |
| IN FRONT OF CHAMBER | | | | | | |
| Unfiltered | .00861 | 8.285 | .3659 | .07133 | .2499 | .18 |
| Filtered | .00783 | 9.016 | .3659 | .07060 | .1689 | .18 |
| INSIDE OF CHAMBER | | | | | | |
| Unfiltered | .01090 | 1.789 | .3201 | .01950 | Many | |
| Filtered | .00063 | 1.281 | .3354 | .00081 | Many | |

NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)




FIG. 67


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC./VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
INSIDE CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 68

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 69

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 70

# SEVEN FOOT WIDE CHAMBER
## (SOLID BOTTOM)

WINDSPEED: 7-10 mph. DIRECTION: South south west

CHAMBER WIDTH: 7 feet DATE: 2/25/72

ATTENUATION (1- VARIANCE RATIO(CHAMBER(BW)/REMOTE)): 85.8%

RUN NUMBER: 2,S11,f NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 222.74 | 2.978 | .5031 | 663.32 | .2279<br>1.8417<br>.4011<br>.5642<br>1.0217 | .20<br>.61<br>.87<br>1.04<br>1.22 |
| BOTTOM | 146.21 | 3.088 | .5031 | 451.50 | 2.1990<br>1.7115<br>.5219<br>.3390 | .40<br>.61<br>1.10<br>1.22 |
| PRESSURES: REMOTE | .00472 | 3.004 | .6098 | .01418 | 1.3289<br>1.9057<br>.3233<br>.8912<br>.7730 | .21<br>.49<br>.76<br>1.04<br>1.23 |
| IN FRONT OF CHAMBER | .00067 | 2.646 | .5945 | .00177 | 2.0769<br>1.8620<br>.3108<br>.7936<br>.4628 | .38<br>.50<br>.76<br>1.10<br>1.22 |
| INSIDE OF CHAMBER | .00965 | 3.059 | .6098 | .0295 | .3094<br>.8306<br>2.4789<br>.4497<br>.7184<br>.6880 | .18<br>.35<br>.50<br>.76<br>1.02<br>1.23 |

NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)




FIG.71

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 72

WINDSPEED: 10-12 mph. DIRECTION: South south west

CHAMBER WIDTH: 7 feet DATE: 2/25/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW)/REMOTE)): 84.9%

RUN NUMBER: 2,S11,e NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 272.22 | 3.490 | .4878 | 950.05 | .283<br>.424<br>.705 | .85<br>1.01<br>1.22 |
| BOTTOM | 207.93 | 4.458 | .4573 | 926.95 | .354<br>.373 | 1.01<br>1.20 |
| PRESSURES: REMOTE | .00491 | 3.159 | .5793 | .01551 | 1.467<br>.803<br>.704<br>.722 | .21<br>.35<br>1.02<br>1.22 |
| IN FRONT OF CHAMBER | .00074 | 2.597 | .5793 | .00192 | 2.063<br>1.901<br>.676<br>.533<br>.338 | .40<br>.49<br>1.01<br>1.11<br>1.20 |
| INSIDE OF CHAMBER | .00916 | 3.329 | .5793 | .03049 | .704<br>.848<br>.569 | .38<br>.99<br>1.22 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
REMOTE STATION
IN FRONT OF CHAMBER
INSIDE CHAMBER
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC./VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 73

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 74

WINDSPEED: 15 mph. DIRECTION: South

CHAMBER WIDTH: 7 feet DATE: 2/25/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW/REMOTE)): 38.9%

RUN NUMBER: 1,s4,b NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 237.24 | 6.805 | .4268 | 1614.4 | .7918 | .66 |
| BOTTOM | 351.72 | 7.798 | .4268 | 2742.71 | .4202 | .66 |
| PRESSURES: REMOTE | .00175 | 3.902 | .5031 | .00683 | 1.400<br>0.564 | .30<br>1.01 |
| IN FRONT OF CHAMBER | .00107 | 7.292 | .3963 | .00780 | None | |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 75

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 76

WINDSPEED: 15 mph. ( 25 gust) DIRECTION: South

CHAMBER WIDTH: 7 feet DATE: 2/25/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW)/REMOTE)): 62.8%

RUN NUMBER: 1,S10,a NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 423.91 | 6.414 | .4268 | 2718.83 | .2265 @<br>.7620 @<br>.2182 @<br>.2811 @ | .20<br>.59<br>.85<br>1.23 |
| BOTTOM | 367.39 | 7.992 | .4116 | 2936.18 | .3642<br>.2592<br>.2237<br>.1847 | .59<br>.73<br>.85<br>1.19 |
| PRESSURES: REMOTE | .00277 | 1.474 | .4900 | .00408 | 2.80<br>.6461<br>.4027<br>1.0123<br>.4497 | .2134<br>.73<br>.85<br>1.07<br>1.22 |
| IN FRONT OF CHAMBER | .00103 | 6.060 | .4116 | .00624 | .2278<br>.2780 | .73<br>.85 |
| INSIDE OF CHAMBER | .00410 | 3.383 | .4116 | .01387 | 1.4864<br>1.0962<br>.4943<br>.3715<br>.4096 | .59<br>.73<br>.85<br>1.02<br>1.22 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
INSIDE CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 77


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
INSIDE CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 77

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 78

WINDSPEED: 15-18 mph. DIRECTION: South

CHAMBER WIDTH: 7 feet DATE: 2/25/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW)/REMOTE)): 15.7%

RUN NUMBER: 1,S4,c NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 216.67 | 8.744 | .4421 | 1894.56 | .5174 | .67 |
| BOTTOM | 342.16 | 9.417 | .4421 | 3222.12 | .2719 | .67 |
| PRESSURES: REMOTE | .00083 | 5.039 | .4878 | .00418 | 1.494<br>.212 | .34<br>.96 |
| IN FRONT OF CHAMBER | .00070 | 7.029 | .4268 | .00492 | None | |
| INSIDE OF CHAMBER | .00103 | 7.714 | .4268 | .00795 | 1.181<br>.151<br>.133 | .26<br>.67<br>.88 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
INSIDE CHAMBER
.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 79

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 80

WINDSPEED: 18-20 mph. DIRECTION: South

CHAMBER WIDTH: 7 feet DATE: 2/25/72

ATTENUATION (1- VARIANCE RATIO(CHAMBER(BW)/REMOTE)): 23.3%

RUN NUMBER: 1,S5,d NO. DATA POINTS: 512

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 113.89 | 6.991 | .4573 | 796.20 | .972 | .67 |
| BOTTOM | 161.75 | 7.780 | .4573 | 1258.41 | .596 | .66 |
| PRESSURES: REMOTE | .00043 | 4.946 | .4878 | .00213 | .424<br>.231<br>.181 | .21<br>.90<br>1.36 |
| IN FRONT OF CHAMBER | .00033 | 5.325 | .4116 | .00176 | .355<br>2.436<br>.227<br>.227 | .21<br>.55<br>.84<br>1.37 |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC./VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG.81

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG.82

WINDSPEED: 35 mph DIRECTION: South

CHAMBER WIDTH: 7 feet DATE: 3/1/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW)/REMOTE)): 47.1%

RUN NUMBER: 4,S9,i NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 1874.96 | 5.408 | .3659 | 10,139.8 | None | |
| BOTTOM | 2768.12 | 6.235 | .3506 | 17,259 | .1369 | .78 |
| PRESSURES: REMOTE | .01857 | 5.902 | .3354 | .10960 | 1.9134 (filtered D.C.) .6076 | .12 .50 |
| IN FRONT OF CHAMBER | .00982 | 8.447 | .3506 | .08295 | .1417 | .78 |
| INSIDE OF CHAMBER | .01105 | 2.539 | .39634 | .02806 | Many? | ? |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERPOSITION OF INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
INSIDE CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 83

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 84

WINDSPEED: 35mph DIRECTION: South

CHAMBER WIDTH: 7 feet DATE: 3/1/72

ATTENUATION (1- VARIANCE RATIO(CHAMBER(BW)/REMOTE)): 48.0%

RUN NUMBER: 4,S11, j NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 2485.81 | 6.684 | .3811 | 16,615.2 | .1326 | .76 |
| BOTTOM | 3444.08 | 7.101 | .3659 | 24,456.4 | None | |
| PRESSURES: REMOTE | .01626 | 7.289 | .3201 | .11852 | None (filtered D.C.) | |
| IN FRONT OF CHAMBER | .00845 | 8.478 | .3506 | .07164 | .1983 | .78 |
| INSIDE OF CHAMBER | .01044 | 1.66 | .2744 | .01733 | Many | |


NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERIMPOSED INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
REMOTE STATION
IN FRONT OF CHAMBER
INSIDE CHAMBER
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 85

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 86

WINDSPEED: 35-40 DIRECTION: South south west

CHAMBER WIDTH: 7 feet DATE: 2/27/72

ATTENUATION (1- VARIANCE RATIO(CHAMBER(BW)/REMOTE)): -13.3%

RUN NUMBER: 3,S10,h NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 3125.43 | 7.173 | .3963 | 22,418.7 | .2931<br>.1786 | .66<br>1.33 |
| BOTTOM | 3600.45 | 7.806 | .3811 | 28,105.2 | .1238 | 1.33 |
| PRESSURES: REMOTE | .00879 | 4.598 | .3506 | .04042 | .4225<br>1.4034<br>.5950<br>.7068 | .15<br>.49<br>.75<br>1.33 |
| IN FRONT OF CHAMBER | .00996 | 9.212 | .3659 | .09175 | .2166<br>.1716<br>.2550 | .17<br>.78<br>1.33 |
| INSIDE OF CHAMBER | .01944 | 3.670 | .3811 | .07134 | .8785<br>.7216<br>.8188<br>.4400<br>1.9037 | .15<br>.61<br>.76<br>1.22<br>1.34 |

NORMALIZED SMOOTHED SPECTRAL ESTIMATE VERSUS FREQUENCY FOR SUPERIMPOSED INCIDENT AND REFLECTED WAVES (FIXED MONITORING STATIONS)




FIG. 87

FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.




FIG. 88

WINDSPEED: 35-40 (gusts 50) DIRECTION: S/SSW

CHAMBER WIDTH: 7 feet DATE: 2/27/72

ATTENUATION (1- VARIANCE RATIO (CHAMBER(BW)/REMOTE)): -10.7%

RUN NUMBER: 3,S3,g NO. DATA POINTS: 1024

| TYPE OF MEASUREMENT | VARIANCE $\sigma^2$ | PEAK $S(fu)/\sigma^2$ | PEAK FREQ. | 50 LAG PEAK $S(fu)$ | SECONDARY $S(fu)/\sigma^2$ | SECONDARY fu |
|---|---|---|---|---|---|---|
| FORCES: TOP | 2154.68 | 7.815 | .3963 | 16,838.8 | .0887<br>.2393 | .15<br>.67 |
| BOTTOM | 3227.33 | 8.333 | .3963 | 26,893.3 | .1149 | .67 |
| PRESSURES: REMOTE | .00798 | 5.547 | .3659 | .04427 | .3082<br>.5977<br>.6345 | .15<br>.76<br>1.37 |
| IN FRONT OF CHAMBER | .00883 | 9.636 | .3659 | .08509 | .1869<br>.2861 | .17<br>1.37 |
| INSIDE OF CHAMBER | .01229 | 5.789 | .3811 | .07115 | 1.1999<br>2.2619 | .15<br>1.37 |


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
REMOTE STATION
IN FRONT OF CHAMBER
INSIDE CHAMBER

FIG. 89


FREQUENCY DISTRIBUTION OF FORCE NON-DIMENSIONALIZED
BY THE VARIANCE. TOP CANTILEVER BEAM ASSEMBLY.
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 90

# APPENDIX II

Spectral plots in front of the breakwater and at the remote station are superimposed for representative wind conditions. Both curves, on each plot, are non-dimensionalized to the variance at the remote station. The figures are presented in order of increasing windspeed; the five foot wide chamber without bottom first, then the five foot with solid bottom, followed by the seven foot wide chamber with solid bottom. Notice that, though the peaks of each curve vary for different wind conditions , the portion of the curves which appear to have more energy in front of the breakwater than at the remote station only occur near the resonant frequency of the chamber as enumerated in the analysis.

Figures 91-100 Chamber width= five feet; no bottom

Figures 101-116 Chamber width= five feet; solid bottom

Figures 116-126 Chamber width= seven feet; solid bottom


WINDSPEED: 20 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: P.O. 12-(114/115)-3
ATTENUATION*: 4%
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 91


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 20 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: L7 12-106/107
ATTENUATION*: <0 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 92


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 20 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: LY 12-108/109
ATTENUATION*: 25 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 93


OUTER GAGES
WINDSPEED: 20 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: L7 12-108/109-6
ATTENUATION*: 60%
* 1-`VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG.94


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 20 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: L7 12-104/105
ATTENUATION*: 0 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 95


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED:30-35M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: L7 11-102/103
ATTENUATION*: 26.6 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 96


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 30-35 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: JN 11-(92+93)
ATTENUATION*: 50%
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 97


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
OUTER GAUGES
WINDSPEED: 30-35 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: JN 11-(92+93)
ATTENUATION*: 50%
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 98


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 30-35 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: RJ 10-(82+83)
ATTENUATION*: 56 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 99


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
OUTER GAUGES
WINDSPEED: 30-35 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: NONE
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: RJ 10-(82+83)-6
ATTENUATION*: 37 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .4 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 100


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 15 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: VK 7-(65+66)
ATTENUATION*: 0 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 101


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR. @∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 15 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: 40 7-(57+58)
ATTENUATION*: 55 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 102


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED:20-25 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: QN 2-(3+4)
ATTENUATION*: 0 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 103


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED:~30 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: 40 5-(34+35)
ATTENUATION*: 51 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 104


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 35 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: 87 3-(5+6)
ATTENUATION*: 56 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG.105


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 35 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: 87 4-(9+10)
ATTENUATION*: 17.3 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 106


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR. @∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 45-50 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: 87 5-(25+26)
ATTENUATION*: 72 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.

FIG. 107


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 10 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: o
ATTENUATION*: 70.9%
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG.108


WINDSPEED: 12-15 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: n
ATTENUATION*: 63 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 109


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 15 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: m
ATTENUATION*: 58.1 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG.110


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC./VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED:18-20 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: τ
ATTENUATION*:63.8%
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG.111


WINDSPEED: 18-20 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: s
ATTENUATION*: 45 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 112


WINDSPEED: 20 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: 1
ATTENUATION*: 54.2%
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 113


WINDSPEED: 20 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: P
ATTENUATION*: 44 %
* 1- VARIANCE RATIO (INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG.114


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED:20-25M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: 9
ATTENUATION*: 56.3 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG.115


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 30 M.P.H.
CHAMBER WIDTH: 5 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: k
ATTENUATION*: 32.3%
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .43 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 116


WINDSPEED:7-10 M.P.H.
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: f
ATTENUATION*:85.8 %
* 1- VARIANCE RATIO -
(INFRONT/REMOTE)
RESONANCE: f = .365 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG.117


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
WINDSPEED:10-12 M.P.H.
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: e
ATTENUATION*: 85 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .365 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 118


WINDSPEED: 15 M.P.H.
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: b
ATTENUATION*: 39 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .365 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)
NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)

FIG. 119


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 15 M.P.H.
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: a
ATTENUATION*: 62 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .365 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG.120


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC./VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 15-18 M.P.H.
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: c
ATTENUATION*: 16 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .365 CYC/SEC.
Remote Station (∞ )
In Front of Chamber (BW)

FIG. 121


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR.@∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 18-20 M.P.H.
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: d
ATTENUATION*: 23.3 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .365 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 122


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR. @∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 35 M.P.H.
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: i
ATTENUATION*: 47 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .365 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 123


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC./VAR. @∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 35 M.P.H.
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: j
ATTENUATION*: 48 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .365 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG. 124


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR. @∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED: 35-40 M.P.H.
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: h
ATTENUATION*: -13.3%
* 1-VARIANCE RATIO
(INFRONT/REMOTE
RESONANCE: f = .365 CYC/SEC.

FIG. 125


NORMALIZED SMOOTHED SPECTRAL EST. (FT.SQ.-SEC.)/VAR. @∞
0.00
1.20
2.40
3.60
4.80
6.00
7.20
8.40
9.60
0.00
0.30
0.60
0.90
1.20
1.50
FREQUENCY (CYC/SEC.)
WINDSPEED:35-40 M.P.H.(GUSTS-50)
CHAMBER WIDTH: 7 FEET
BOTTOM: SOLID
POROSITY: .293
EFF. FETCH: 2.8 MILES
RUN NO.: 8
ATTENUATION*: -10 %
* 1- VARIANCE RATIO
(INFRONT/REMOTE)
RESONANCE: f = .365 CYC/SEC.
Remote Station (∞)
In Front of Chamber (BW)

FIG.126

# APPENDIX III

Representative digitized data records.

DATA RECORDS USED IN APPENDIX I

| Digital Run Number | Analog Run No. | Spectra | Tape & Rec. | Output | Calibration Top Force | Bottom Force | Remote Pressure | Near Pressure | Inside Pressure |
|---|---|---|---|---|---|---|---|---|---|
| a | 1 | S10(9/13 & 9/14) | 743 | IT | 1.015 | .971 | -.00344 | .00151 | .00513 |
| b | 1 beg. | S 4(4/ 1 & 4/ 2) | 27 | JH | .957 | 1.008 | -.00349 | .00147 | .00525 |
| c | 1 mid. | S 4(4/ 4 & 4/ 5) | 27 | JH | .957 | 1.008 | -.00349 | .00147 | .00525 |
| d | 1 end | S 5(4/ 6 & 4/ 7) | 27 | JH | .957 | 1.008 | -.00349 | .00147 | |
| e | 2 beg. | S11(8/ 5 & 8/ 6) | 743 | JH | 1.015 | .971 | -.00577 | .00256 | .0086 |
| f | 2 + | S11(8/ 7 & 8/ 8) | 743 | WY | 1.015 | .971 | -.00577 | .00256 | .0086 |
| g | 3 beg. | S 2 S 3(6/12 & 6/13) | 27 | WY | .957 | 1.008 | -.00349 | .00248 | .0088 |
| h | 3 beg. | S10(9/11 & 9/12) | 743 | WY | 1.015 | .971 | -.00344 | .00256 | .0086 |
| i | 4 beg. | S 9(8/ 1 & 8/ 2) | 743 | WY | 1.015 | .971 | -.00344 | .00256 | .0086 |
| j | 4 beg.+ | S11(8/ 3 & 8/ 2) | 743 | AI | 1.015 | .971 | -.00344 | .00256 | .0086 |
| k | 5 | S 8(3/ 3 & 3/ 4) | 325 | AI | 1.000 | 1.000 | -.00336 | .0025 | .0086 |
| l | 11 beg. | S 6(7/ 1 & 7/ 2) | 966 | AI | 1.116 | 1.047 | -.00354 | .0027 | |
| m | 11 mid. | S 7(7/ 3 & 7/ 4) | 966 | AI | 1.116 | 1.047 | -.00354 | .0027 | |
| n | 11 end | S 7(7/ 5 & 7/ 6) | 966 | AI | 1.116 | 1.047 | -.00354 | .0027 | |
| o | 12 mid. | S 7(7/ 7 & 7/ 8) | 966 | MM | 1.116 | 1.047 | -.00354 | .0027 | |
| p | 13 beg. | S 7(7/ 9 & 7/10) | 966 | MM | 1.116 | 1.047 | -.00354 | .0027 | |
| q | 13 night after | S 7(7/11 & 7/12) | 966 | MM | 1.116 | 1.047 | -.00354 | .0027 | |
| r | 14 | (7/13 & 7/15) | 966 | MM | 1.116 | 1.047 | -.00354 | .0027 | |
| s | 14 mid. | (7/15 & 7/16) | 966 | MM | 1.116 | 1.047 | -.00354 | .0027 | |

# APPENDIX IV

## SUMMARY OF FORCE FLUCTUATIONS ON POROUS WALL

Background: A 3.3 foot section of the porous chamber wall was cantilevered at the top (3' above SWL) and bottom (7' below SWL) and the fluctuating forces resulting from the net effect of the wave action on both sides of the wall were recorded and analysed. (For details see ref. pp. 36,40,45,51,52,55,58 and 79).

Attached are the measured maximum values of force for the cases shown in APPENDIX I. To use this information the following points may be helpful:

*"MAX FORCE EXERTED TOWARD BRIDGE" refers to the maximum force recorded during a record due to a low chamber level and wave crest outside chamber. "MAX FORCE MEASURED AWAY FROM BRIDGE" occurs during some cycle of the record when the chamber is relatively full and the wave in front of the wall is near a trough.

*Each forch listed should be DIVIDED BY 3.3 to produce the force per unit length of porous wall.

*Notice that the peak values for the top and bottom of the panel NEED NOT OCCUR at the same time thus the total peak force is $F_{Total} - \frac{1}{3.3} F_{Top} + F_{Bottom}$ . The maximum value of the sum of the forces at a given instant of time was found to be 118 pounds per linear foot of wall (ref. p. 81). Should the need exist for knowing the sum of the top and bottom forces at a given time the data is available but extremely time consuming to digest.

*APPENDIX I (  ref) contains spectral plots proportional to the frequency distribution of the peak force squared and non-dimensionalized by a mean force squared. These curves are intended primarily to visually demonstrate the frequency distribution of the force. The use of the attached tables should allow calculations where maximum values are desired independent of frequency. It can be noted that if the spectral plot is the only available information, a rough estimate of the max force can be arrived at as follows:

$$\frac{[\text{Max force toward bridge}] + [\text{Max force away}]}{2} = 2[S(f\ )/\ ^2]$$

FIVE FOOT CHAMBER W/SOLID BOTTOM

(Measured Resultant on 3.3' Panel)

| Pg | Wind Speed Direction | MAX FORCE EXERTED TOWARD BRIDGE | MAX FORCE MEASURED AWAY FROM B. | |
|---|---|---|---|---|
| 134 o | 10 | Top 44.72 | 31.16 | All numbers correspond to the peak value monitored at the top & bottom of a 3.3 foot long test section. |
| | S | Bot 39.77 | 45.04 | |
| 137 n | 12-15 | Top 46.31 | 38.51 | Also note that the time at which the peak force occurred for the top and bottom beam need not coincide. |
| | S | Bot 47.03 | 50.34 | |
| 140 m | 15 | Top 64.92 | 53.38 | |
| | S | Bot 66.79 | 76.65 | |
| 143 r | 18-20 | Top 159.72 | 89.15 | |
| | S | Bot 93.98 | 107.05 | |
| 146 s | 18-20 | Top 121.25 | 107.53 | |
| | S | Bot 118.32 | 118.30 | |
| 149 l | 20 | Top 64.42 | 54.99 | |
| | S.S.W. | Bot 63.87 | 63.85 | |
| 152 p | 20 | Top 70.43 | 52.32 | |
| | S.S.W. | Bot 72.17 | 72.31 | |
| 155 g | 20-25 | Top 93.16 | 84.23 | |
| | S.S.W. | Bot 103.45 | 96.53 | |
| 158 k | 30 | Top 266.77 | 230.23 | |
| | S | Bot 112.16 | 126.94 | |
| | | Top | | |
| | | Bot | | |

SEVEN FOOT CHAMBER W/SOLID BOTTOM

(Measured Resultant on 3.3' Panel)

| Pg | Wind Speed Direction | MAX FORCE EXERTED TOWARD BRIDGE | MAX FORCE MEASURED AWAY FROM B. | |
|---|---|---|---|---|
| 164 f | 7-10 S.S.W. | Top 41.21<br>Bot 42.20 | 44.06<br>44.03 | Note: all numbers correspond to the peak VALUE monitored at top and bottom of a 3.3 foot long test section. |
| 167 e | 10-12 S | Top 44.01<br>Bot 47.40 | 55.46<br>47.76 | Also note that the time at which the peak force occurred for the top beam need not coincide with the bottom beam. |
| 170 b | 15 S | Top 57.60<br>Bot 70.49 | 62.98<br>76.47 | |
| 173 a | 15 (25 gust) S | Top 67.83<br>Bot 58.67 | 65.13<br>83.78 | |
| 176 c | 15-18 S (S.S.W.?) | Top 50.78<br>Bot 48.74 | 54.11<br>60.50 | |
| 179 d | 18-20? S (S.S.W.?) | Top 34.67<br>Bot 38.33 | 37.10<br>40.99 | |
| 182 i | 35 S | Top 177.5<br>Bot 213.2 | 150.4<br>188.8 | |
| 185 j | 35 S | Top 250.40<br>Bot 162.70 | 215.42<br>236.10 | |
| 188 h | 35-40 S.S.W. | Top 244.6<br>Bot 200.2 | 164.5<br>235.8 | |
| 191 g | 35-40 (50 gust) S.S.W. | Top 190.97<br>Bot 142.06 | 126.42<br>112.07 | |