

Contract Number \_\_\_\_\_

HMA mix design ID number(s) to be used for production \_\_\_\_\_

**Additive Technology Description**

Name of additive manufacturer or producer \_\_\_\_\_

Additive Product Name \_\_\_\_\_

Additive Intended Purpose      Reduce Optimum Mixing Temperature      Compaction Aide

Description of product or process \_\_\_\_\_

Water/Foaming      Organic Additive      Chemical Additive      Other \_\_\_\_\_

Manufacturer or producer's recommended additive dosage rate \_\_\_\_\_

Contractor's target additive dosage rate \_\_\_\_\_

<b>Manufacturer or Producer's Recommendation</b>	<b>Temperature (°F)</b>
Maximum mixing temperature for HMA when using additive	
Maximum discharge temperature for HMA when using additive	
Maximum asphalt binder temperature when using additive	

\*The Contractor's maximum mixing temperature cannot exceed the maximum mixing temperature recommended by the manufacturer of the additive nor the optimum mixing temperature +25°F per Section 5-04.3(8).

Submitted by \_\_\_\_\_

Paving Contractor

Paving Contractor Representative - Signature

Reviewed by \_\_\_\_\_  
Contracting Agency Representative - Signature

No exceptions taken

Revise and resubmit

Not acceptable

Reminder: The truck ticket shall identify the material (product or process) used in production of HMA.

Required Attachments:      Additive Manufacturer's catalog cuts  
   Additive Manufacturer's Recommendations for production